

TIP – Verification of Pile Integrity and Capacity

George Piscsalko P.E.

Pile Dynamics, Inc.

PÅLDAG 17

May 4, 2017

**It is obvious why we test;
we cannot afford failures**



Thermal Integrity Profiling

Measures the elevated temperatures during the hydration process to determine pile integrity

Temperature during curing is directly related to concrete quality, volume, and radius (cover)

- Reductions in temperature indicate necking, inclusions, or poor quality concrete
- Increases in temperature indicate bulges or increased concrete cover

Variance in temperature between diametrically opposite wires indicates cage alignment/cover issues

Acquiring Volume data allows temperature to be converted to radius

Thermal Integrity Profiling

• Thermal Integrity Profiler evaluates concrete both inside and outside the cage


- Assessing both cover and alignment

(100% testing – entire section)

• Evaluates shaft during curing (as early as 12 hrs. depending upon mix design and pile diameter)

- Allows construction to progress much faster
- Significant cost savings can be achieved if we can save many days or weeks on a project



ASTM D7949




*Convection
to air*




*Conduction
to soil*



Thermal Integrity Profile




Data Interpretation - Local Defect near C2




Toe Correction

Temperature (F)




Toe Correction


Temperature (F)




Thermal Integrity Profiling




1 hour



4.5 hours




8 hours




18 hours


Thermal Integrity Profiling




2 hours



4.5 hours



8 hours



18 hours

TIP Testing Equipment


- Thermal Wire® cable
 - Embedded in grout or concrete
 - Digital sensors sample temperature data
- TAP or TAG Box
 - Data collection with TAP
 - Data collection and transmission to cloud
- TIP Main Unit
 - Project set up
 - Download data from TAP box
 - View field results



Acceptance Criteria

- Load carrying requirements can be controlled by:
 - Geotechnical side shear
 - Structural bending
 - Compression
- These are directly related to:
 - Circumference surface area of the shaft
 - Moment of inertia
 - Cross sectional area
- Radius Reduction approach will affect each differently:
 - Reduction has linear relation to circumference
 - Reduction has fourth power relation to moment of inertia
 - Reduction has squared relation to area

Radius Reduction vs. Capacity Reduction



Acceptance Criteria

| Radius Reduction | Bending Capacity Loss | Compression Capacity Loss | Side Shear Reduction | Cover Loss (4 inch cover, 6ft dia. shaft) |
|------------------|-----------------------|---------------------------|----------------------|--|
| 3% | 11% | 6% | 3% | 1.08in |
| 6% | 22% | 12% | 6% | 2.16in |
| >6% | >22% | >12% | >6% | >2.16in |

Satisfactory (S)

**0 to 6% Radius Reduction and
Local Cover Criteria Met**

Anomaly (A) Requiring further evaluation

**Radius Reduction > 6% or
Local Cover Criteria Not Met**



I-5 Bridge over Puyallup River Tacoma, Washington




TIP Example 1

- Wet cast Shaft in Washington State
- 3m diameter
 - 10 TIP wires installed
- Cage Diameter 2.6m
- 38.4m shaft length
- TIP testing begins immediately after casting
 - Data recorded during pour as well as cure
- Data recorded for approximately 90 hours after casting
- Shaft peak temperature occurs approximately 40 hours after casting
- Shaft analysis done at time of one half peak temperature (20 hours)

TIP Data at Peak Temperature




TIP Data at one half Peak Temperature



Coring Results at approximately 90' depth

- Coring result close to wires 7 and 8, where largest reduction occurred
- Coring confirms TIP test results
- Zone was hydro-blasted and pressure grouting was performed



TIP Results and Acceptance Criteria


- Shaft shows a local reduction near wires 6 through 9
 - Design radius = 1.5m
 - Local effective radius at wires 7 & 8 = 1.02m
 - Reduction in Local Radius = 32.2%
 - Clearly greater than 6% Reduction in our Criteria
 - Cover is also reduced to zero in these regions
 - Anomaly extends inside the reinforcing cage
 - Below minimum cover requirement
 - Shaft fails BOTH the radius reduction criteria AND the cover criteria
 - This is considered an anomaly which requires further evaluation
 - Coring and remediation is done in several locations in the shaft

Example 2: Free fall concrete into wet base

Shaft Details:
Diameter 2.4m
Length 12.8m

What is wrong with this shaft?

- Engineer requested that contractor to use tremie (request denied)
- Concrete placed free fall method
- Reportedly 1.5m of water present at the base prior to placement
- Core revealed collapsed shaft and contaminated concrete



Dynamic Testing Drilled Shafts

- Build up Pile Top and use a plywood cushion
 - Reduces Excavation
 - Protects Reinforcing
 - Remove after Testing
- Use Steel Top Transducer
 - Strain sensors attached to steel pipe
 - Eliminates uncertainties in Area and Modulus
 - Accelerometers attach directly to the Drilled Shaft
- Drop Weight 1%, 2%, ... 5% of R_u
 - 2% helps to activate end bearing




Built-up Section



Steel Shell Extension

Sensors

Use of Load Cell




Force Measurement made on Steel Pipe

Thick cushion

Thin cushion

Acceleration on Pile

Drilled Shaft Testing




Large Drop Weight

Thick Cushion

Steel top transducer

Strain gages attached to top transducer

Drilled Shaft



Data Transmission from Sensors to PDA

Thin cushion

Accelerometers attached directly to drilled shaft

Dynamic Testing Result

Estimated Static Load - Set Curve




CAPWAP and TIP on a 2.1 m diameter drilled shaft

TIP Measurements



CAPWAP impedance



Conclusions

- TIP is being used frequently for testing drilled shafts and ACIP/CFA piles
- TIP can evaluate the entire cross-section including the area outside the reinforcing cage
- An acceptance criteria based upon cover and radius is possible with TIP
- The minimum cover specs for a project can be verified
- Dynamic Testing is being done regularly on Drilled Shafts
 - TOP Transducer eliminates errors due to unknown area and modulus
- When doing a dynamic test on a drilled shaft, TIP can provide additional information to help with the CAPWAP analysis

Thank You

